

Thank you for purchasing an Outdoor Revolution product, this product will give years of satisfactory service if basic instructions are followed, our products are designed for durability and for ease of erection.



MOVEAIRLITE CLASSIC ANNEXE INSTRUCTIONS & CARE MANUAL

WWW.OUTDOOR-REVOLUTION.COM

UNIT 1 BRICK PARK
BRETFIELD COURT
BRETTON STREET INDUSTRIAL ESTATE
DEWSBURY
WEST YORKSHIRE
WF12 9BY



IMPORTANT: PLEASE CHECK YOUR EQUIPMENT

1 X FLYSHEET (OR OUTER)

1 SINGLE INFLATION POINT AIRFRAME TUBE

1 X INNER TENT

1 X BAG OF PEGS

1 X REPAIR KIT

1 X CARRYING BAG



We highly recommend that you insure your annexe against storm damage or accidental damage, as the warranty does not cover such eventualities. The manufacturer IS NOT liable for any damage caused to the annexe or its contents because of misuse, incorrect pitching or extreme weather.
(Full warranty details are at the back of this booklet)

THE WARRANTY (CONTINUED...)

- Flaws in the fabric caused by excessive use
- Imperfections and pulls in mesh doors due to wear and tear
- Water ingress through fabric as a result of UV degradation
- Water ingress through seams caused by excessive abrasion of seams or taped seam
- Broken zips caused by over tensioning, forcing or snagging
- Over tensioned/stretched seams coming apart
- Buckles subjected to undue force or abrasion
- Lost/popped out eyelets
- Broken holdalls
- Pole breakages or tube punctures (where applicable)
- Collateral damage from a pole breakage
- UV degradation
- Condensation, (a natural occurrence, exacerbated by insufficient ventilation opening)
- Consequential damage/loss to property/belongings (either inside or outside of the product) or shortening of holidays

Outdoor Revolution work very closely with our retail partners to manage all warranty repairs/issues:

**Please contact your retailer immediately (even if purchased online) if you feel your Outdoor Revolution product has a genuine warranty issue. The retailer, in turn will raise the issue with ourselves and we will action; with the retailer, according to the nature of the claim.

**Please ensure the product is clean and dry and as close to its original condition as possible before sending back for checking.

**Wet or dirty products will not be accepted back for checking/warranty claims.

** It is important to note that the Sales Contract between yourself and the retailer you purchased the Outdoor Revolution product from, remains valid throughout any warranty claim and your statutory rights are not affected.

OUTDOOR REVOLUTION GUARANTEE

Outdoor Revolution products are designed and produced to the highest manufacturing standards. The best quality fabrics and components available are used for each specific item and a rigorous checking process of finished products is in place.

All finished products are:-

- Checked for and are free of minor defects
- Are fit for the purpose/use that they are intended
- Are of a satisfactory quality

It is important that correct care is taken when opening the product, erecting, using and just as importantly, packing away the product. Following these rules will keep your product in reliable working condition for many years. Failure to adhere to these simple guidelines may cause unnecessary damage to the product (see formal instructions for hints and tips on handling/erecting the product). A repair kit is included in the product to help resolve any minor issues.

THE WARRANTY

The Outdoor Revolution Warranty lasts for 12 months from the original date of purchase (please keep all receipts or copies of any relevant transaction to substantiate the purchase date). The warranty only covers workmanship and fabric/components. Any faults found within 6 months of purchase will be investigated by Outdoor Revolution. Faults found outside of the initial six months of purchase will need to be proven by you the purchaser, in line with current consumer legislation after the short term right to reject has ended.

Retailer will not refund a purchase if no fault is found.

Product warranty must be registered **BEFORE** use via www.outdoor-revolution.com and as soon as possible from the date of purchase.

The manufacturer's warranty does not cover the following:-

- General wear and tear over extended periods of use or seasonal pitching of the product
- Accidental damage caused by but not exclusive to, humans, animals or weather

IMPORTANT INFORMATION

- ◆ Please do not leave for your holiday without fully erecting and checking you have all the contents for your annexe. If you are missing anything please contact your retailer immediately before use.
- ◆ Please also note that manmade fabrics are prone to condensation when the warm air and moisture inside the annexe comes into contact with the colder outside of the annexe fabric. You may also experience condensation in the tube sleeves. This is a perfectly natural occurrence and should not be confused with leaking. Ensure all Vortex Vents are open whenever possible to help combat condensation.
- ◆ Ideally erect your annexe for some period before use - allowing it to weather. 'Weathering' can take a few uses of the annexe before it is fully effective. Seam sealant can be used to solve any persistent weeps. This process is completely normal.
- ◆ Make sure before erecting, that you site the annexe on clear level ground with no sharp objects underneath and that all the zips are fully closed. (We recommend laying a groundsheet down to keep the annexe dry and clean).
- ◆ We suggest conducting a trial run of your annexe to familiarise yourself with the set up and use of the annexe. If you have any issues relating to pitching your annexe please contact your dealer for help before going on holiday.
- ◆ Please note this annexe is designed as a 'touring' annexe and not for permanent pitch.
- ◆ After use always dry and air the annexe before packing away to prevent mildew or mould.
- ◆ Any dirt or stains can be removed by brushing or gently washing with warm water. DO NOT use detergents as this will destroy the waterproofing on the fabrics.
- ◆ DO NOT cook or smoke in this annexe; although the outer fabric is flame retardant treated it will still melt.
- ◆ In the event of damage; please contact your retailer. If for whatever reason you are unable to contact them please email cs@blue-diamond-products.co.uk and our customer service team will be happy to assist.

OPTIONAL ACCESSORIES

- ◆ Trio Sleeping Bags - Super comfortable sleeping bag range designed to complement the MoveAirLite Annexe
- ◆ Trio Sleeping Pillow - Pillow to match the Trio Sleeping Bag Range
- ◆ Visit www.outdoor-revolution.com for more information on the optional extras.

TROUBLE SHOOTING

<u>PROBLEM</u>	<u>REASON</u>	<u>SOLUTION</u>
The Air tube keeps deflating after removing the	The Dynamic Speed Valve button hasn't been pressed back out.	Press the quick release button back out to shut the valve.
The annexe is leaking.	The annexe requires weathering two or three times before it fully seals itself so you may experience a little bit of weeping. This could also be condensation, an inevitable occurrence.	Allow the annexe to get wet then dry two or three times. Open all the vents to increase air flow and reduce condensation.
Bowing and twisting of the tubes.	The tubes can twist inside the sleeves, particularly when packing away so next time the tube bows.	Unzip the sleeve whilst the tube is deflated and re-position the tube.

IN THE EVENT OF A PUNCTURE

If you have a small puncture in your Air Frame Tube you can easily repair it using the standard puncture repair kit.

- ◆ To remove the Air Frame Tube - deflate the tube and then unzip the two protective sleeves over the tube and pull the Air Tube out. Do not unzip the sleeves whilst the tube is inflated.
- ◆ Locate and repair the puncture on the Air Frame Bladder.
- ◆ Place the Air Tube back in to the sleeves in the correct place with the valves in the valve hole. Make sure the Tube is straight and not twisted.
- ◆ Zip the two sleeves back up fully.
- ◆ Inflate the AirFrame Tube again, ensuring that the puncture has now been repaired.
- ◆ If this process doesn't work you may have to buy a new bladder.

****Spare AirFrame Bladders can be bought to replace damaged ones. Visit the Spares Section at www.outdoor-revolution.com or contact us on 01924 455313****

****Awnings will not be replaced because of damaged bladders****

PACKING AWAY YOUR AWNING

- ◆ Unpeg the guy lines and most of the pegs around the annexe leaving the four corners pegged out.
- ◆ Open the Dynamic Speed Valve press in the quick release button. Leave the button pressed in to allow all the air to escape as you roll it.
- ◆ Unpeg the four corners and un-zip the annexe from the awning door.
- ◆ Lay the annexe flat on the ground and push as much air out of it as possible.



1. Fold the annexe lengthways from the opposite ends to the valves to push all the air out. Make a long thin sausage shape.



2. Measure the width of the bag up against the width of the folded annexe to make sure the annexe is going to fit.



4. Place the rolled annexe on to the bag and pull the sides up round it. Finally, zip up the bag.



PLEASE READ THE INSTRUCTIONS CAREFULLY

TIP: Refer to the photograph to help when pitching your **MoveAirLite Annexe**

1. Spread the annexe flysheet out on the ground next to your MoveAirLite awning with the zip next to the door you wish to attach it to.



2. Zip out the door panel on the MoveAirLite Classic Awning on the side you wish to attach the annexe. Stow the door panel away somewhere dry and clean.

3. Zip the Annexe zip on to the door zip, ensuring you don't pull the material too viciously and making sure no material gets caught in the zip.



4. Locate the Dynamic Speed Valve and ensure the valve is **closed** before attaching the pump. (The valve is closed when the button is pressed out)

5. Next, attach the pump to the Dynamic Speed Valve and begin to carefully inflate taking care that no part of the fabric is caught anywhere.



6. Inflate the AirFrame until you can give it a good squeeze. The tube needs to have room inside for air to expand. Don't worry if you do keep inflating - the Intelligent Frame will release any excess air. (Please note the Intelligent Frame is set to a limit of 5.5psi before it will release air).

7. Replace the cap on the Dynamic Speed Valve and cover the valves with the flap to prevent water getting inside.



8. Peg out and tension the front of the annexe. Use the adjustable pegging straps to tension the annexe as you desire. Make sure you don't over tension the fabric. If it is too tight, release some tension.

9. Lay the inner tent in the annexe and start at the back by clipping the 'c' clips to the floor and matching the coloured elastic with the coloured loop.



10. Work your way round the inner tent clipping all the elastics and clips in. Work your way forward till the inner tent is fully clipped in.

10. Peg out all the guylines around the annexe to ensure it is secure.



11. Finally - put all your sleeping equipment inside the annexe and enjoy your holiday!

WARNING: Never unzip the zips on the protective sleeves whilst the AirFrame Tubes are inflated. This will result in the tube bursting or ballooning out of the sleeve causing damage to the tube and the sleeve. This is not covered under the warranty.